



State Environment Impact Assessment Authority, M.P.
(Government of India, Ministry of Environment & Forests)

Environmental Planning Coordination Organization (EPCO)
Paryavaran Parisar, E-5. Arera Colony
Bhopal-4620 16
visit us <http://www.mpseiaa.nic.in>
Tel:0755-2466970, 2466859
Fax : 0755-2462136

No: 1598 /SEIAA/2016

Date: 24.5.16

To,
Shri Naveen Mehta, Director,
M/s Orange Infracon Pvt. Ltd.,
UG-21, BCM Heights,
Scheme No. 54, Indore (M.P.)-452010
Mob. No. 9425082648, E-mail : n.mehta@rediffmail.com

Sub:- Case No. 5006/2016: Prior Environment Clearance for Expansion of High Rise Residential Project "BCM Park" at Khasra No.-10/8, 11, 12/2/8-Min2, 38-Min2 & 39/3/7-Min-4, & 39/3/7-Min5, Village Pipliya Kumar, Tehsil & District-Indore (M.P.), land area 11570 sqmt. (1.157 ha), Total Built-up Area-53349.75 sq.m. (existing Built-up Area-19221.84 sq.m., proposed built up area 34127.91 sqmt.) by Shri Naveen Mehta, Director, M/s Orange Infracon Pvt. Ltd., UG-21, BCM Heights, Scheme No. 54, Indore (M.P.)-452010, Environment Consultant: EQMS India Pvt. Ltd., Delhi

Ref:- Your application dtd. 21.01.2016 received in SEIAA office on 23.02.2016.

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O.1533(E),dtd.14.09.06 & its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings, ppt & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee(SEAC)& State Environment Impact Assessment Authority(SEIAA) constituted by the competent Authority.

- (i). The proposed project is a expansion of High Rise Residential Project "BCM Park" having total built up area 53349.75 sq.m. The project comes under category (B) for project activity 8(a) of schedule of EIA Notification, 2006 because total construction is between 20000 sqm &150000 sqm & plot area is less than 50 ha.
- (ii). As per Joint Director Town & Country Planning, Indore (9957 dtd 25.07.2015) the total land area is 11570 sq.m. for high rise building at Village Pipliya Kumar, Tehsil & District-Indore (M.P.) and 780.00 sqmt. for EWS at Village-Lasuidya Mori, Tehsil & District-Indore (MP). As per Khasra Panchsala 2014-2015 the land is in the name of M/s Orange Infracon Pvt. Ltd. The project includes four residential blocks with S+6 floors (Block A, B, C & E), club block (Block D-G +1), EWS block basement and other allied facilities.
- (iii). The source of water supply is Indore Municipal Corporation (letter dtd. 06.10.2015). The total water requirement is 212 KLD (102 KLD-Existing & 110 KLD- Expansion). The fresh water requirement is 142.5 KLD. The waste water

(Ajatshatru Shrivastava)
Member Secretary

Case No. 5006/2016

Issued vide letter no. 1598-99 dated 24.5.16


Case No.: To be quoted in registered cases for correspondence

generation is 167 KLD (67 KLD-Existing & 100 KLD- Expansion) and STP capacity is 190 KLD. The available treated water is 150.5 KLD which is proposed to be 69.5 KLD recycled and remaining 81 KLD is proposed to be disposed in sewer line (Nagar Nigam, Indore letter dtd. 01.02.2016).

- (iv). The Municipal Solid Waste 697 kg/day (Existing- 292 Kg/day and after expansion - 405 Kg/day) shall be generated which is proposed to be segregated at source and the biodegradable and non- recyclable/ non biodegradable waste will be stored and collected separately. Colored collection bins shall be provided in proper numbers. PP has proposed door to door collection system for collection of domestic waste and MSW storage room provided at surface (basement) for temporary storage. The non-recyclable and non-biodegradable waste, sludge from STP is proposed to be used for horticultural purpose as manure. Final disposal through Municipal Corporation Indore (Indore Municipal Corporation letter dtd. 10.02.2016).
- (v). The maximum height of the building is 45 M (existing-18 m after expansion-27m). PP has provided Front MOS 21 m and side / rear MOS 10.5 m.
- (vi). PP has proposed to provide underground fire water storage tank, Fire pumping system, Yard Hydrant System, Wet Riser System, portable Fire extinguisher, automatic Sprinkler System, automatic fire detection system & Fire Alarm system. etc. as per NBC 2005.
- (vii). PP has proposed to provide 324 ECS (171 ECS-Basement & 153 ECS Stilt/Podium) and additional visitors parking at surface.
- (viii). The total power requirement is 1184 KVA. The source of electricity is Madhya Pradesh Kshetra Vidyut Vitran Company Limited. PP has also provided power back up 1 No. DG set of 320 kVA. For control of energy PP has proposed solar energy for common area (1/3 of area), LED for common area lighting (2/3 of area), CFL for internal lighting, solar heater etc.
- (ix). PP has proposed to provide roof top rain water harvesting system with 06 nos. of recharging pits.
- (x). PP has proposed an area of 3672 sq m (31.73% of plot area, i.e. 11570 sq m) to be developed as green area including 660 no. of trees.

Based on the information submitted at Para i to x above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its **324th meeting held on 26.04.2016** and decided to accept the recommendations of **SEAC meetings 273rd dtd 01.04.2016**.

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14th September 2006 & its amendments to the expansion of High Rise Residential Project "BCM Park" at Khasra No.-10/8, 11, 12/2/8-Min2, 38-Min2 & 39/3/7-Min-4, & 39/3/7-Min5, Village Pipliya Kumar, Tehsil & District-Indore (M.P.), land area 11570 sqmt. (1.157 ha), Total Built-up Area-53349.75 sq.m. (existing Built-up Area-19221.84 sq.m., proposed built up area 34127.91 sqmt.) by Shri Naveen Mehta, Director, M/s Orange Infracon Pvt. Ltd., UG-21, BCM Heights, Sch. No. 54, Indore (M.P.)-452010 with following Specific Conditions as recommended by SEIAA & SEAC in its meetings along with the Standard Conditions enclosed at **Annex-I**.


(Ajatshatru Shrivastava)
Member Secretary

Case No. 5006/2016

Issued vide letter no. 1598-99 dated 24.5.16


Case No.: To be quoted in registered cases for correspondence

A. Specific Conditions as recommended by SEIAA

- (1) The entire demand of water should be met through Municipal Corporation; Indore there should be no extraction of ground water.
- (2) PP should ensure linkage with municipal sewer line for disposal of waste water.
- (3) Municipal Solid Waste:
 - (a) Provide compactors for MSW.
 - (b) Ensure three bin systems for segregated collection of waste.
 - (c) Ensure to proper provision for lifting the solid waste from storage area.
 - (d) Ensure linkage with Municipal Corporation for final disposal of MSW.
- (4) PP should ensure road width at least 30 m; Front MOS 15 m and side / rear MOS 7.5 m. road width; MOS and Open spaces as per MPBVR 2012 rule 42 (2) for building height upto 45m.
- (5) For firefighting:
 - (a) PP should ensure connectivity to the fire station from the project site.
 - (b) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Nagar Nigam, Indore) incorporating all the fire fighting measures recommended in National Building Code Part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Nagar Nigam only after ensuring that all fire fighting measures are physically in place.
- (6) PP should ensure the rain water harvesting. In addition, PP should provide recharging trenches. The base of the trenches should be Kachha with pebbles.
- (7) PP should ensure installation of photovoltaic cells (solar energy) for lighting in common areas, LED light fixtures, and other energy efficient equipments.
- (8) PP should ensure car parking as per MPBVR 2012.
- (9) Green belt :-
 - (a) PP should ensure plantation to the 3672 sq m (31.73% of plot area, i.e. 11570 sq m) as per the proposed landscape plan. Plantation should be done in two rows all along the periphery of the project area including Avenue plantation along the roads, trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar etc. along with ornamental varieties.
 - (b) PP should ensure to initiate plantation in the project site during construction.
 - (c) Every effort should be made to protect the existing trees on the plot.

B. Specific Conditions as recommended by SEAC

- (1) Fresh water requirement for the project shall not exceed 142.50 KLD.


(Ajatshatru Shrivastava)
Member Secretary

Case No. 5006/2016

Issued vide letter no. 159899 dated 24.5.16

Case No.: To be quoted in registered cases for correspondence

- (2) The excess treated water will be used for watering of municipal road side green area or efforts shall be made to supply this water to the construction sites for use in the construction works.
- (3) Peripheral plantation all around the project boundary shall be carried out using tall saplings of minimum 2 meters height of species which are fast growing with thick canopy cover preferably of perennial green nature. As proposed in the landscape plan & EMP a minimum of 660 numbers of trees will be planted in residential area. PP will also make necessary arrangements for the causality replacement and maintenance of the plants.
- (4) STP sludge shall be filter-pressed and the de-watered sludge shall be disposed off with the MSW.
- (5) Power back-up for un-interrupted operations of STP shall be ensured.
- (6) CFL/LED should be preferred over of tube lights.
- (7) Fund should be exclusively earmarked for the implementation of EMP.
- (8) MSW storage area should have 48 hours storage capacity.
- (9) Dual plumbing should be provided.
- (10) Provision for physically challenged persons be made so that they easily excess pathway/derive way for their vehicles.
- (11) Provisions shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after completion of the period.
- (12) PP will obtain other necessary clearances/NOC from concerned authorities.

Standard Conditions - Encl: Annex-I

(Ajatshatru Shrivastava)
Member Secretary

1599
Endt No. / SEIAA/ 2016

Date 24.5.16

Copy to:- (1) Principal Secretary, Urban Development & Environment Deptt. 3rd Floor, Mantralaya Vallabh Bhawan, Bhopal.

- (2). Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- (3). Member Secretary, MPPCB, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- (4). The Collector, District Indore -M.P.
- (5). The Commissioner, Municipal Corporation, Indore, MP
- (6). The Jt. Director, Town & Country Planning, Housing Board Complex, A.B. Road, Indore (M.P.)
- (7). Director, I.A. Division, Monitoring Cell, MoEF, Gol, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi – 110 003
- (8). Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- (9). Guard file.

Encl: Standard Conditions (Annex-I)

(Ajatshatru Shrivastava)
Member Secretary

Case No. 5006/2016

Issued vide letter no. 1598-99 dated 24.5.16

Case No.: To be quoted in registered cases for correspondence

State Environment Impact Assessment Authority, M.P.


(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran, Parisar, E-5, Arera Colony, Bhopal-4620 16


Annex-I


Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA
notification, 2006
(Building/ construction projects / area development projects & township)

A. Construction Phase

1. The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
5. A First Aid Room will be provided in the project both during construction and operation of the project.
6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
9. Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.
10. Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge


1 of 6


Issued vide No. 1598-99
Dated 24.5.16


State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
13. Wastewater generated from temporary labour tents will be diverted to the sewer network in the area.
14. No water logging should take place at any point during construction phase.
15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
16. As far as possible ready mixed concrete should be used in construction work.
17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/MPPCB.
19. Storm water control and its use should be as per CGWB and BIS standards for various applications.
20. Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
21. Care shall be taken during the wet drilling activities.
22. Spread of contaminated water should be prevented by installing temporary barriers of G.I. Sheets.
23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
24. On-site burning of waste material will not be permitted.
25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
26. Commitment towards CSR have to be followed strictly.
27. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge

2 of 6

Issued Vide No. SEIAA/EPCO
1528-20
24.5.16
AA/EPCO

State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)


Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16


28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
29. To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
30. Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightning etc.

B. Operation Phase

1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, GoI before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
2. Treated waste water should not be used for air conditioning.
3. Treatment of 100% grey water by decentralized treatment should be done.
4. The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
5. Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
6. The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madhya Pradesh Pollution Control Board.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge

3 of 6


Issued Under No. 150899/EP/CO
Dated: 24/5/18


State Environment Impact Assessment Authority, M.P.


(Government of India, Ministry of Environment & Forests)

Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Aera Colony, Bhopal-4620 16

8. No water logging should take place at any point during operation phase.
9. The Project Proponent shall explore the possibility of using solar energy wherever possible.
10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam, 1984.
11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
12. Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
14. Rain water harvesting for roof run-off and surface run-off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
15. The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
17. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, Gol in three months time.
18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
19. The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
20. The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
21. Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge

4 of 6


Issued Under No. 59859/MA/ERCO
Dated 24/5/16


State Environment Impact Assessment Authority, M.P.


(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

C. Others

1. All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
2. All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
3. All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
4. Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
5. The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, GoI, and its Regional Office located at Bhopal.
6. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
7. The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
8. The project proponent shall also submit six monthly reports on 1st June and 1st December of each calendar year on the status of compliance of the stipulated EC conditions including results of monitored data to the regulatory Authority in hard and soft copies.
9. The Regional Office, MoEF, GoI, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report, Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, GoI at Bhopal and MPPCB.
10. The Project Proponent shall inform to the Regional Office, MoEF, GoI, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
11. In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
12. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge


5 of 6


Issued Vide No. 1508-99 SEIAA/EPCO
Date: 24.5.16
A.A/EPCO


State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NO_x (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.
17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.
20. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.


(Dr R P Singh)
Officer-in-Charge


(Dr Vinita Vipat)
Officer-in-Charge


(Dr Sadhna Tiwari)
Officer-in-Charge

6 of 6