



**State Environment Impact Assessment Authority, M.P.  
(Government of India, Ministry of Environment & Forests)**

Environmental Planning Coordination Organization (EPCO)  
Paryavaran Parisar, E-5. Arera Colony  
Bhopal-4620 16  
visit us <http://www.mpseiaa.nic.in>  
Tel:0755-2466970, 2466859  
Fax : 0755-2462136

No: 4710 /SEIAA/2016  
Date: 13-12-16

To,  
Mr. Kishan Widhani, Project Engineer,  
M.P Police Housing Corporation Ltd,  
D-30, HIG Colony, AB Road,  
Indore – (M.P.) 452001

**Sub:- Case No. - 5309/2016:** Prior Environment Clearance for proposed "Multi-Storey Residential Complex for Police Personnel" at 15th Battalion, Khasra No. – 128, 135, 136, Village – Gadar Khedi, Tehsil & Distt. - Indore, (M.P.) Total Plot Area – 6.22 ha. (62230.03 sqm), Total Built-up Area - Revised – 1,43,602.78 sqm).by Mr. Kishan Widhani, Project Engineer, Madhya Pradesh Police Housing Corporation Ltd, D-30, HIG Colony, AB Road, Indore – (M.P.) 452001 Env. Consultant. – Greencindia Consulting Pvt. Ltd. Ghaziabad (U.P.)

**Ref:** Your application dtd. 18.07.16 received in SEIAA office on 20.07.2016

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14<sup>th</sup> September 2006 and its amendments, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings, ppt & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- (i). The proposed project is Construction of Multi-Storey Residential Complex for Police Personnel having total built up area 1,43,602.78 sq. m. and land area is 62230.03 sq.m. The project comes under 8(a) category (B) of schedule of EIA Notification, 2006 & its amendments because total construction is between 20,000 sq.m & 1, 50,000 sq. m and plot area is less than 50 ha.
- (ii). As per T & CP, Indore (vide letter no.5729 dtd 14.07.2016), out of the 12.922 ha total land area only 6.128 ha is allocated for the proposed project at Village – Gadar Khedi, Tehsil & District. - Indore, (M.P.). As per Khasara Panchsala 2014-15 the land is the name of 15th Battalion Police Personnel Force Indore. The project includes 10 Constable blocks (G+14) with 1180 units, 04 Non Gazette Officer Block with 472 units, Community Center (G+4) etc.
- (iii). The source of water supply is Municipal Corporation, Indore (letter dtd. 09.02.16). The total water requirement is 769.8 KLD (fresh water 549.9 KLD).

Case No. 5309/2016

Issued vide letter no. .... dated .....

Case No.: To be quoted in registered cases for correspondence



The waste water generation is 600.4 KLD and STP capacity is 720.6 KLD with MBBR technology. The available treated water is 480.3 KLD, out of which 219.9 KLD shall be recycled & 260.4 KLD will be disposed in municipal sewer line.(IMC letter dtd. 15.02.2016).

- (iv). The MSW (3809.3 kg/day) shall be generated including Horticulture Waste and Street Sweeping. The generated biodegradable and non biodegradable waste will be collected separately. Closed room with concrete surface will be constructed for solid waste storage. The bio degradable waste will be subjected to Organic Waste Convertor and the compost produced will be used as manure for landscaping and non-biodegradable waste will be deposited at a landfill site of Municipal Corporation Indore.(IMC letter dtd. 27.01.2016)
- (v). PP has proposed the maximum height of the building as 45 m. PP has provided Road width 30m; Front MOS 18 m and side / rear MOS 9.0 m. PP has submitted the NOC of the Civil Aviation Department for high rise building.
- (vi). PP has proposed to provide Wet riser Fire Hydrant System, automatic sprinkler system, Fire water reserve (under-ground storage tanks) as well as fire water pumps to take auto start in case of pressure drop in hydrant system, the Fire pumps shall be as one Diesel driven pump and Two electrically driven pumps with one jockey pump, manual fire alarm system etc. as per NBC 2005 . PP has also submitted the fire fighting plan duly incorporating the circulation space all around the proposed construction for the fire tenders.
- (vii). PP has proposed to provide 1051 ECS (Open- 1037 ECS, Stilt – 14 ECS).It was observed that PP has proposed maximum no. of car parking in open area instead of stilt and basement.
- (viii). The total power requirement is 8750 KVA. The source of electricity is Madhya Pradesh Kshetra Vidyut Vitran Company Limited. PP has also proposed 4 no DG set of capacity 4\*650 = 2600 KVA (for common areas and essential services only). For energy conservation measures PP has proposed the buildings will be designed to ensure that natural ventilation, Solar Lighting for street and other common places and reflecting Paints for roof tops.
- (ix). PP has proposed to provide roof top rain water harvesting system with 06 nos. of recharging pits.
- (x). PP has proposed an area of 8295 sq. m (13.5%) to be developed as green area by planting 600 no. of trees and species of Saltree, Kachnar, Kadam, Neem, Gulmohar etc. It is observed that there are 119 numbers of existing trees in the project area. PP has submitted a tree conservation plan, in which he proposes to cut 55 trees and retain 64 trees. PP also propose to plant 1200 additional trees in lieu of the trees cut for the proposed development of the project.
- (xi). PP has submitted the use of the existing 3 play grounds within their campus for use of the children and the families to be accommodated in the proposed buildings.
- (xii). PP has committed to increase the internal road widths from 6m to 7.5m.



Based on the information submitted at Para i to xii above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 385<sup>th</sup> meeting held on 16.11.2016 and decided to accept the recommendations of **SEAC meetings** 283<sup>rd</sup> dtd. 27.10.2016.

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14<sup>th</sup> September 2006 & its amendments to the Proposed "Multi-Storey Residential Complex for Police Personnel" at 15th Battalion, Khasra No. – 128, 135, 136, Village – Gadar Khedi, Tehsil & District. - Indore, (M.P.) Total Plot Area – 6.22 ha. (62230.03 sqm), Total Built-up Area - 43,602.78 sq.m. by Mr. Kishan Widhani, Project Engineer, Madhya Pradesh Police Housing Corporation Ltd, D-30, HIG Colony, AB Road, Indore – (M.P.) 452001 subject to the compliance of the Standard Conditions enclosed at **Annex-I** and the following additional Specific Conditions as recommended by SEIAA & SEAC in its meetings.

**A. Specific Conditions as recommended by SEIAA**

- (1) The entire demand of water should be met through Municipal Corporation, Indore there should be no extraction of ground water.
- (2) The inlet and outlet point of natural drain system should be maintained with adequate size of channel for ensuring unrestricted flow of water.
- (3) **Disposal of waste water.**
  - (a) PP should ensure linkage with municipal sewer line for disposal of waste water as committed the letter dtd. 15.02.16.
  - (b) The treated wastewater of 480.3KLD shall be recycled and reused for flushing (173.5 KLD) and gardening (41.5 KLD) Miscellaneous (4.9KLD) to reduce the demand of fresh water.
  - (c) Ensure regular operation and maintenance of the STP.
  - (d) The Project Proponent shall explore the possibilities of reusing the treated wastewater from nearby projects during rainy season.
- (4) The final disposal point for storm water will be municipal storm drain if storm water network is present. If storm water network is absent, the storm water surface runoff should be disposed off in proper way. The budget should be including in EMP plan for storm water management.
- (5) **Solid Waste Management:**
  - (a) Provide compactors for MSW.
  - (b) Separate wet and dry bins must be provided at the ground level for facilitating segregation of waste.
  - (c) The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- (6) PP should ensure road width, front MOS and side / rear as per MPBVR 2012 and increase the internal road widths from 6m to 7.5m as proposed.



(7) **For firefighting:-**

- (a) PP should ensure connectivity to the fire station from the project site.
- (b) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Municipal Corporation, Indore) incorporating all the fire fighting measures recommended in National Building Code Part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Municipal Council only after ensuring that all fire fighting measures are physically in place.

(8) **For Rain Water Harvesting, and Ground water recharge:-**

- (a) PP should ensure the rain water harvesting with **06 nos** of recharging pits and these pits should be connected laterally to consume the surplus runoff. In addition, PP should provide recharging trenches. The base of the trenches should be Kachha with pebbles.
- (b) Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 4 mts. above the highest ground water table.
- (c) The unpaved area shall be more than or equal to 20% of the recreational open spaces.

(9) PP should ensure to provide car parking as proposed ECS (Open- 1037 ECS, Stilt – 14 ECS).

(10) **For Energy Conservation PP should Ensure :-**

- (a) Use of LED lights in the common areas, landscape areas, and boundary compound walls etc.
- (b) Solar lights provide for common amenities like Street lighting & Garden lighting.
- (c) For power back up ensure to provide 04 no. DG set capacity of 4\*650 = 2600 KVA (for common areas and essential services only)
- (d) PP should also ensure to adopt energy conservation measure as per the latest State Govt. Policy for generating roof top solar energy and make use of the subsidies to be granted as per the policy. Any surplus generation from solar energy should be ploughed back in the grid to generate additional revenues for the proposed RWA.

(11) **Air Quality and Noise:-**

- (a) Dust, smoke & debris prevention measures such as wheel washing, screens, barricading & debris chute shall be installed at the site during construction including plastic/tarpaulin sheet covers for trucks bringing in sand & material at the site.
- (b) The exhaust pipe of the DG set if installed must be minimum of 10mtr away from the building or in case it is less than 10m away, the exhaust pipe shall be taken up to 6m above the building.



(12) **Green belt :-**


- (a) PP should ensure plantation by planting 1200 nos of trees in two rows in periphery, along the road, around open space area, parking area and other amenities. Trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar, Saptparni etc. should be planted.
  - (b) Every effort should be made to protect the existing trees Pipal, Neem and Imli on the plot.
  - (c) PP should obtain permission from concerned authority to cut the trees and plant additional trees as compensatory.
  - (d) Explore the possibility to retain more than 64 numbers of trees.
  - (e) The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
- (13) In the case of future expansion in the scope or any changes(s) in the scope of the project shall again require Prior Environmental Clearance as per EIA notification, 2006.
- (14) The project authorities shall earmark adequate funds to implement the conditions stipulated by SEIAA/SEAC along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.

**B. Specific Conditions as recommended by SEAC**

- (15) Fresh water requirement for the project shall not exceed 549.91 KLD.
- (16) The excess treated water will be used for watering of municipal road side green area or efforts shall be made to supply this water to the construction sites for use in the construction works.
- (17) Peripheral plantation all around the project boundary shall be carried out using tall saplings of minimum 2 meters height of species which are fast growing with thick canopy cover preferably of perennial green nature. As proposed in the landscape plan & EMP a minimum of 600 no. of trees will be planned. PP will also make necessary arrangements for the causality replacement and maintenance of the plants.
- (18) PP should also explore the possibility of providing phyto-remediation based treatment system for pre-treatment of waste water as sufficient land is available in the project.
- (19) STP sludge shall be filter-pressed and the de-watered sludge shall be disposed off with the MSW.
- (20) Power back-up for un-interrupted operations of STP shall be ensured.
- (21) CFL/LED should be preferred over of tube lights and solar panels should be provided on the roofs as proposed by the PP during presentation.
- (22) Fund should be exclusively earmarked for the implementation of EMP.
- (23) MSW storage area should have 48 hours storage capacity.



- (24) Dual plumbing should be provided.
- (25) Provision for physically challenged persons be made so that they easily excess pathway/derive way for their vehicles.
- (26) Provisions shall be made for the housing of construction labor within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after completion of the period.
- (27) PP will obtain other necessary clearances/NOC from respective authorities.
- (28) PP will comply with all the commitments made by the letter no. Q2/PE/MPPHC/Indore/2016-17 dated 27/10/2016.
- (29) PP will explore the possibility of providing more parking in the ground floor instead to open parking to leave open space for play ground / landscape.


  
 (Anupam Rajan)  
 Member Secretary

Endt No. 4711/ SEIAA/ 16  
 Copy to:-

Date 13-12-16

- (1). Principal Secretary, Urban Development & Environment Deptt. 3<sup>rd</sup> Floor, Mantralaya Vallabh Bhawan, Bhopal.
- (2). Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- (3). Member Secretary, MPPCB, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- (4). The Collector, Distt- Indore -M.P.
- (5). The Commissioner, Municipal Corporation, Indore, MP
- (6). The Jt. Director, Town & Country Planning, Housing Board Complex, A.B. Road, Indore (M.P.)
- (7). Director, I.A. Division, Monitoring Cell, MoEF, GoI, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi – 110 003
- (8). Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- (9). Guard file.

**Encl: Standard Conditions (Annex-I)**

  
 (Dr. Sanjeev Sachdev)  
 Officer-in-Charge



State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)  
Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran, Parisar, E-5, Arera Colony, Bhopal-462016


Annex-I.


Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA  
notification, 2006


(Building/ construction projects / area development projects & township)

A. Construction Phase.

1. The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
5. A First Aid Room will be provided in the project both during construction and operation of the project.
6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
9. Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.
10. Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.

  
(Dr R P Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge

  
(Dr Sadhna Tiwari)  
Officer-in-Charge


1 of 6




State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)  
Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
13. Wastewater generated from temporary labour tents will be diverted to the sewer network in the area.
14. No water logging should take place at any point during construction phase.
15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27<sup>th</sup> August, 2003.
16. As far as possible ready mixed concrete should be used in construction work.
17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/MPPCB.
19. Storm water control and its use should be as per CGWB and BIS standards for various applications.
20. Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
21. Care shall be taken during the wet drilling activities.
22. Spread of contaminated water should be prevented by installing temporary barriers of G.I. Sheets.
23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
24. On-site burning of waste material will not be permitted.
25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
26. Commitment towards CSR have to be followed strictly.
27. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

  
(Dr R.P. Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge

  
(Dr Sadhna Tiwari)  
Officer-in-Charge

2 of 6



State Environment Impact Assessment Authority; M.P.


(Government of India, Ministry of Environment & Forests)  
Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016


28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
29. To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
30. Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightning etc.

B. Operation Phase

1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, GoI before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
2. Treated waste water should not be used for air conditioning.
3. Treatment of 100% grey water by decentralized treatment should be done.
4. The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
5. Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
6. The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madhya Pradesh Pollution Control Board.

  
(Dr R P Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge

  
(Dr Sadhna Tiwari)  
Officer-in-Charge


3 of 6





State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)  
Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

8. No water logging should take place at any point during operation phase.
9. The Project Proponent shall explore the possibility of using solar energy wherever possible.
10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam, 1984.
11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
12. Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
14. Rain water harvesting for roof run-off and surface run-off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
15. The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
17. A Report on the energy conservation measures confirming to energy conservation norms finalized by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, GoI in three months time.
18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
19. The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
20. The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
21. Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

  
(Dr R P Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge


  
(Dr Sadhna Tiwari)  
Officer-in-Charge





State Environment Impact Assessment Authority, M.P.  
(Government of India, Ministry of Environment & Forests)  
Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

C. Others

1. All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
2. All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
3. All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
4. Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
5. The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, Gol, and its Regional Office located at Bhopal.
6. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
7. The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
8. The project proponent shall also submit six monthly reports on 1<sup>st</sup> June and 1<sup>st</sup> December of each calendar year on the status of compliance of the stipulated EC conditions including results of monitored data to the regulatory Authority in hard and soft copies.
9. The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report, Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, Gol at Bhopal and MPPCB.
10. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
11. In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
12. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.

  
(Dr R P Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge

  
(Dr Sadhna Tiwari)  
Officer-in-Charge





State Environment Impact Assessment Authority, M.P.


(Government of India, Ministry of Environment & Forests)

Research and Development Wing, Madhya Pradesh Pollution Control Board,  
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO<sub>2</sub>, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
16. The environmental statement for each financial year ending 31<sup>st</sup> March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.
17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at [www.mpseiaa.nic.in](http://www.mpseiaa.nic.in) and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.
20. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

  
(Dr R P Singh)  
Officer-in-Charge

  
(Dr Vinita Vipat)  
Officer-in-Charge

  
(Dr Sadhna Tiwari)  
Officer-in-Charge

6 of 6