

# State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment & Forests)

Environmental Planning Coordination Organization (EPCO)
Paryavaran Parisar, E-5. Arera Colony
Bhopal-4620 16
visit us http://www.mpseiaa.nic.in
Tel:0755-2466970, 2466859

Fax: 0755-2462136

No: 6315 /SEIAA/2015 Date: 14-10-15

To, Shri Baldev Khemani, Partner, Sahib Developers, LB Enterprises, Jumerati Chowk, Bhopal (MP)-462001

Sub: Case No. 2747/2015 Prior Environment Clearance for proposed Project "Prithivi Courtyard" at Khasra No. 418/2, 428, 429/1, 429/2, 430/1, 430/2, 431/1, 431/2, Village -Samardha Kaliyasot, Tehsil-Huzur, District-Bhopal (M.P.); Total Land Area- 3.919 ha, Total Built-up Area — 35564.36 sq.m. by Shri Baldev Khemani, Partner, Sahib Developers, LB Enterprises, Jumerati Chowk, Bhopal (MP)-462001, Ph.No. 9303131215, <a href="mail-sahibdevlopersbhopal@gamil.com">Enviro Consultant Save Green, Bhopal</a>.

Ref: Your application dtd. 16.04.2015 received in SEIAA office on 16.04.2015

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14<sup>th</sup> September 2006 and its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings, ppt & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- (i). The proposed project is building & construction residential project "Prithivi Courtyard" having total built up area 35564.36 sq.m. The project comes under 8(a) category (B) of schedule of EIA Notification, 2006 because total construction is between 20,000 sq.m & 1,50,000 sq.m and plot area is less than 50 ha.
- (ii) As per Joint Director Town & Country Planning, Bhopal (vide letter dtd.21.09.2010 & 07.11.2013) the total land area is 3.919 ha (39190.0 Sq.m.) at Village -Samardha Kaliyasot, Tehsil-Huzur, District-Bhopal, MP. As per Khasara Panchsala 2014-2015 the land is in the name of Baldev Khemai, Pallavi Khemani, Madhu Khemani and Yashwant Khemani. A partnership deed executed on 13.10.2010 & amendment deed on 05.04.2014 between all the landowners under the firm M/s Sahib Developers. The project includes Flats 250; Duplexes-103; EWS- 42 & casual shop (G+2).

(Ajatshatru Shrivastava) Member Secretary

Case No. 2747/2015
Issued vide letter no. 6.3.15-16... dated 1.4:10:10
Case No.: To be quoted in registered cases for correspondence

- (iii). The source of water supply is Municipal Corporation, Bhopal (letter dtd. 13.03.2015). The total water requirement is 207 KLD (fresh water 114 KLD). The waste water generation is 184.3 KLD and STP capacity is 200 KLD (100 KLD-2 Nos). The available treated water is 154 KLD, out of which 119.2 KLD shall be recycled & 34.8 KLD will be disposed in municipal sewer line. (BMC letter dtd. 26.02.15).
- (iv). The MSW (0.799 MT / day) is proposed to be collected in bins of three colors (green, blue and dark grey) separate for biodegradable and non biodegradable waste. Final disposal shall be through Municipal Corporation Bhopal (BMC letter dtd. 26.02.2015).
- (v). The maximum height of the building is 18 m + stilt; the road width is 60 m; Front MOS 12 m and side / rear MOS 6.00 m.
- (vi). PP has proposed to provide underground water storage tank, pump control Panel, Portable fire extinguishers, air vessel with pressure switches, Diesel Pumps etc. as per NBC 2005.
- (vii). PP has proposed to provide parking space of 292 ECS (stilt 4350 sqmt. / 30 = 145 ECS; Basement 2850 sqmt. / 35 = 81 ECS; Open 1650 sqmt. / 25 = 66 ECS).
- (viii). The total power requirement is 1638 KW. The source of electricity is MPSEV and solar energy. PP has also provided power back up one DG set 125 KVA. It is proposed to provide LED lights, level controller for pumps, timer for street & common lighting and solar lights for road lighting.
  - (ix). PP has proposed to provide roof top rain water harvesting system with 05 nos. of recharging pits.
  - (x) Out of the total land (3.919 ha) an area of 5287.00 sqmt. (13.59%) was proposed to be developed as green area with 400 nos. of trees including two rows for front area periphery and single row for duplex.

Based on the information submitted at Para i to x above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 234<sup>th</sup> meeting held on 07.09.2015 and decided to accept the recommendations of SEAC meetings 200<sup>th</sup> dtd 30.06.15

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14<sup>th</sup> September 2006 and its amendments to the proposed building construction project "Prithivi Courtyard" at Khasra No. 418/2, 428, 429/1, 429/2, 430/1, 430/2, 431/1, 431/2, Village -Samardha Kaliyasot, Tehsil-Huzur, District-Bhopal (M.P.); Total Land Area- 3.919 ha, Total Built-up Area 35564.36 sq.m. by Shri Baldev Khemani, Partner, Sahib Developers, LB Enterprises, Jumerati Chowk, Bhopal (MP) subject to the compliance of the Standard Conditions enclosed at **Annex-I** and the following additional Specific Conditions as recommended by SEIAA & SEAC in its meetings.

A. Specific Conditions as recommended by SEIAA

(1) The entire demand of fresh water should be met from municipal supply and there should be no extraction of ground water.

(Ajatshatru Shrivastava) Member Secretary

- (2) PP should ensure :-
  - Linkage with municipal sewer line for disposal of extra treated waste water.
  - PP should ensure STP for 200 KLD and accordingly increase the budget.
- (3) PP should provide compactors for MSW and ensure linkage with Bhopal Municipal Corporation for final disposal of MSW
- (4) PP should ensure road width and open spaces as per MP Bhumi Vikas Niyam 2012 rule 42 (1) for building up to 18 m height.
- (5) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Nagar Nigam, Bhopal) incorporating all the fire fighting measures recommended in National Building Code part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Nagar Nigam only after ensuring that all fire fighting measures are physically in place.
- (6) PP should ensure rain water harvesting and increase the no. of recharging pits to 07.
- (7) PP should ensure the car parking for 292 ECS as proposed.
- (8) PP should ensure installation of photovoltaic cells (solar energy) for lighting in common areas, LED light fixtures and energy efficient equipments.
- (9) The Authority decided that PP should ensure :
  - c. Plantation in 5287.00 sqmt. (13.59%) of total plot area (3.919 ha) and plant 600 tree saplings at least 3 years old.
  - d. Plantation should be done in two rows all along the periphery of the project area except the row houses located along the boundary wall where one row of trees should be planted along the boundary of the project area, avenue plantation along the roads, play ground and other amenities area. PP should ensure plantation of big trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar etc along with ornamental varieties.
  - Every effort should be made to protect the existing trees on the plot.
- (10) Hon'ble NGT Central Zone Bench Bhopal in its order dated 30.03.2015 in the original application Nos. 135/2014(CZ) and 48/2014 (CZ), directed that along the river Kaliasot construction activity within 200 m. shall be restricted and beyond 200 m. green land it would be open for the construction activity. Moreover no untreated sewage will be discharged into Kaliasot river and PP has to install requisite STP. PP will have to adhere to the directives of NGT and modify the development and building permissions, if obtained. The respective departments should also be informed to modify the permissions accordingly.

(Ajatshatru Shrivastava) Member Secretary

## B. Specific Conditions as recommended by SEAC

- (11) Fresh Water requirement of the project during operation phase shall not exceed 114 KLD.
- (12) Efforts shall be made to provide Solar based lights in the common spaces including the street lights.
- (13) Provision shall be made for the construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, creche etc. The housing structures to be removed after completion of the project.
- (14) STP sludge to be dewatered using filter press & will be disposed off with the MSW.

Standard Conditions - Encl: Annex-I

(Ajatshatru Shrivastava)
Member Secretary

Endt No. / SEIAA/ 15 Copy to:-

Date 14-10-15

- Principal Secretary, Urban Development & Environment Deptt. 3<sup>rd</sup> Floor, Mantralaya Vallabh Bhawan, Bhopal.
- Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- (3) Member Secretary, MPPCB, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- (4). The Collector, Distt- Bhopal -M.P.
- (5). The Commissioner, Municipal Corporation, Bhopal, MP
- (6) The Jt. Director, Town & Country Planning, Paryavaran Parisar, E-5, Arera Colony, Bhopal, MP
- Director, I.A. Division, Monitoring Cell, MoEF, Gol, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi – 110 003
- (8) Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- (9). Guard file.

Encl: Standard Conditions (Annex-I)

A (Ajatshatru Shrivastava)
Member Secretary

Case No. 2747/2015
Issued vide letter no. 6,315-16... dated 19:10:15
Case No.: To be quoted in registered cases for correspondence

(Government of India, Ministry of Environment & Forests) Research and Dovelopment Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

Annex-I

Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA notification, 2006 (Building/ construction projects / area development projects & township)

#### A. Construction Phase


- The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
- 2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
- 3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile foilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
- 4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
- 5. A First Aid Room will be provided in the project both during construction and operation of the project.
- 6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- 7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- 8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.

Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board

(Dr.R.P. Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

1 of 6



(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

- 11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- 12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- Wastewater generated from temporary leabour tents will be diverted to the sewer network in the area.
- 14. No water logging should take place at any point during construction phase.
- 15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
- 16. As far as possible ready mixed concrete should be used in construction work.
- 17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- 18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/ MPPCB.
- Storm water control and its use should be as per CGWB and BIS standards for various applications.
- Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- Care shall be taken during the wet drilling activities.
- Spread of contaminated water should be prevented by installing temporary barriers of G.I. Sheets.
- 23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
- On-site burning of waste material will not be permitted.
- 25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
- 26. Commitment towards CSR have to be followed strictly.

 Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

(Dr R > Singh 9 4 12 Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

2 of 6

epco epco

Issued Vide No. SEIAA/EPCO

(Government of India, Ministry of Environment & Forests)

Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
- To reduce the electricity consumption and load on air conditioning, high quality-doubleglass with special reflective coating in windows should be promoted.
- Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- 31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- 32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.

#### B. Operation Phase

- 1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, GoI before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
- 2. Treated waste water should not be used for air conditioning.
- Treatment of 100% grey water by decentralized treatment should be done.
- The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
- Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
- The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
- 7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and confirm to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madnya Pradesh Pollution Control Board.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge 3 of 6

Issubdition 19 10 6315 16 VEPCO
Dutellind 14 10 15

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 8. No water logging should take place at any point during operation phase,
- The Project Proponent shall explore the possibility of using solar energy wherever possible.
- -10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam, 1984.
  - 11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
- 13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- 14. Rain water harvesting for roof run- off and surface run- off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- 16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- 17. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, GoI in three months time.
- 18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
- The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 4 of 6

Heenda vincen. 631576 AVIGEO

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

#### C. Others

- 1. All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
- 2. All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- 3. All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- 4. Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
- 5. The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, Gol, and its Regional Office located at Bhopal.
- 6. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
- 7. The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
- 8. The project proponent shall also submit six monthly reports on 1st June and 1st December of each calendar year on the status of compliance of the stipulated EC conditions including results of monitored data to the regulatory Authority in hard and soft copies.
- 9. The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report. Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, GoI at Bhopal and MPPCB.
- 10. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- 11. In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
- 12. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.

(Dr R P Singh)

Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge

is sund Wide on 6315-16 SEL & RPOO I march 19:10:15

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1,991 and EIA Notification, 2006.
- 15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO2, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
- 16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of
- 17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.

20. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

(Dr R P Singh)

(Dr Vinita Vipat) Officer-in-Charge Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

6 of 6