

State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment & Forests)

Environmental Planning Coordination Organization (EPCO) Paryavaran Parisar, E-5. Arera Colony Bhopal-4620 16 visit us http://www.mpseiaa.nic.in

Tel:0755-2466970, 2466859

Fax: 0755-2462136

/SEIAA/2016

To, Shri Anil Khanna, Authorized Signatory, M/s Fortune Builders, Fortune House, 157, Zone-1, M.P. Nagar, Bhopal (M.P.) - 462011

Sub:- Case No. 3061/2015 Prior Environment Clearance for proposed Residential Project "Blue Ridge" at Khasra No.-407, 408/1, 408/2/1, 408/2/2, 412/1, 412/2, 413/1,413/2,414 at Village- Kalapani, Tehsil- Huzur, District - Bhopal (M.P.) Total plot area of 71521.75 sq. m. and Total built-up area of 48,286.235 sq. m. by Shri Anil Khanna, Authorized Signatory, M/s Fortune Builders, Fortune House, 157, Zone-1, M.P. Nagar, Bhopal (MP) 462011 Env. Consultant Das, Lucknow

Ref:- Your application dtd. 18.05.2015 received in SEIAA office on 25.05.2015.

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14th September 2006 and its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings, ppt & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- The proposed project is a building construction of Residential Building (Duplexes) having total built up area 48,286.235 sq.m. The project comes under category (B) for project activity 8(a) of schedule of EIA Notification, 2006 because total construction is between 20,000 sq.m & 1,50,000 sq. m and plot area is less than 50 ha.
- As per Joint Director Town & Country Planning, Bhopal (vide letter 982 dtd 30.01.14) total land area is 7.6 ha out of this 7.32 ha (73248.17 sq. m.) is allocated for the project at Village-Kalapani, Tehsil-Huzur, Distt.-Bhopal (M.P.).
- As per Khasara Panchsala 2014-2015, the land is in the name of Shri Vupendra (iii). Singh. PP has also submitted deed of joint venture which is executed (dtd. 27.03.14) between Vupendra Singh through General Power of Attorney holder Shri Virendra Singh and M/s Fortune Builders through its partners Shri Ajay Mohgaonkar and Shri Sameer Gupta. The project includes construction of Duplexes- 481 and EWS - 66.
- The source of water supply is Bhopal Municipal Corporation (letter dtd. (iv). 21.11.2015). The total water requirement is 479 KLD (fresh water 271 KLD). The

(Ajatshatru Shrivastava) Member Secretary

Case No. 3061/2015

Issued vide letter no. 215752. dated 2.4.616 Case No.: To be guoted in registered cases for correspondence

treated water is 344 KLD for which PP has assured that zero discharge policy will be adopted by reusing the treated waste water in dual plumbing, gardening, road washing and in other construction sites.

- (v). The Municipal Solid waste 1444 kg/day, Horticulture waste 42 kg/day and STP sludge 18 kg/day shall be generated. The generated biodegradable and non biodegradable waste will be collected in two coloured bins (green and blue)at within campus. PP has also proposed provision of 48 hours MSW storages site will be made within the site and for final disposal/treatment of waste, the hired agency will dispose off the waste and STP sludge at designated place of the Municipal site (BMC letter dtd. 13.01.2016)
- (vi). PP has provided total road and circulation space 24384.2 sq.m. (34.09%) with width of 12.0m and 7.50m internal roads.
- (vii). PP has proposed to provide centralized underground water storage tank, sprinklers, fire fighting extinguishers, yard hydrant, fire alarms etc. as per NBC 2005.
- (viii). PP has proposed to provide porch area in each of the duplex for individual car parking with dedicated 41 ECS visitors parking.
- (ix). The total power requirement is 1556 KVA the source is Madhya Pradesh Power Corporation Limited and one DG set of 125 KVA has been proposed for the project. For energy conservation PP has proposed LED in common areas to reduce the load on conventional lighting system, installation of 116 nos. of solar street panel photo electric sensors etc.
- (x). PP has proposed to provide roof top rain water harvesting system with 06 nos. of recharging pits.
- (xi). PP has proposed 10085.5 sq.m area to be developed as green area by including 980 trees (70 nos tall heighted trees and 910 medium heighted trees).

Based on the information submitted at Para i to xi above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 332nd meeting held on 12.05.2016 and decided to accept the recommendations of SEAC meetings 255th dtd 02.01.2016.

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14.09.2006 & its amendments to the proposed Project "Blue Ridge" at Khasra No.-407, 408/1, 408/2/1, 408/2/2, 412/1, 412/2, 413/1,413/2,414 at Village- Kalapani, Tehsil- Huzur, District - Bhopal (M.P.) Total plot area of 71521.75 sq. m. and Total built-up area of 48,286.235 sq. m. by Shri Anil Khanna, Authorized Signatory, M/s Fortune Builders, Fortune House, 157, Zone-1, M.P. Nagar, Bhopal (MP) with following Specific Conditions as recommended by SEIAA & SEAC in its meetings along with the Standard Conditions enclosed at **Annex-I.**

A. Specific Conditions as recommended by SEIAA

(1) The entire demand of water should be met through Municipal Corporation, Bhopal and there should be no extraction of ground water.

> (Ajatshatru Shrivastava) Member Secretary

Case No. 3061/2015

Issued vide letter no 2.1.51.52 dated 2.4.6.16

Case No.: To be quoted in registered cases for correspondence

The same

- (2) The inlet and outlet point of natural drain system should be maintained with adequate size of channel for ensuring unrestricted flow of water.
- Disposal of waste water.
 - (a) PP should ensure the use of extra treated waste water in their construction site and there should be zero discharge of waste water from the project site.
 - (b) PP should obtain clear NOC from Nagar Nigam Bhopal and ensure linkage with municipal sewer line for disposal of waste water whenever municipal sewer line is laid in the project area.
 - (c) When the municipal sewer line is laid in the project area, PP should ensure linkage with municipal sewer line for disposal of extra treated waste water (if any).
- (4) Solid Waste Management:
 - (a) Provide compactors for MSW.
 - (b) Separate wet and dry bins must be provided at the ground level for facilitating segregation of waste.
 - (c) All non-biodegradable waste shall be handed over to authorized recyclers for which a written tie up must be done with the authorized recyclers.
 - (d) Organic waste composter/Vermiculture pit with a minimum capacity of 0.3 kg/tenement/day must be installed.
 - (e) Ensure linkage with Municipal Corporation for final disposal of MSW.
- (5) PP should ensure road width, front MOS and side / rear as per MPBVR 2012.
- (6) For firefighting:
 - (a) PP should ensure connectivity to the fire station from the project site.
 - (b) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Nagar Nigam, Bhopal) incorporating all the fire fighting measures recommended in National Building Code Part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Nagar Nigam only after ensuring that all fire fighting measures are physically in place.
- (7) For Rain Water Harvesting, and Ground water recharge:
 - (a) PP should ensure the rain water harvesting with 6 nos of recharging pits. In addition, PP should provide recharging trenches. The base of the trenches should be Kachha with pebbles.
 - (b) A rain water harvesting plan needs to be designed where the recharge bores (minimum one per 5000 sq mt of built up area) shall be provided. The rain water harvested should be stored in a tank for reuse in household through a provision of separate water tank and pipeline to avoid mixing with potable municipal water supply. The excess rain water harvested be linked to the tube well bore in the premise through a pipeline after filtering arrangement of the rain water.
 - (c) The unpaved area shall be more than or equal to 20% of the recreational open spaces.

(Ajatshatru Shrivastava) Member Secretary

Syc

- (8) Energy:
 - (a) All common area lighting must be of LED/Solar lights.
 - (b) At least 1% of connected applied load generated from renewable energy source such as photovoltaic cells or wind mills or hybrid be provided.
 - (c) As per the provisions of the Ministry of New and Renewable Energy solar water heater of minimum capacity 100 lit/ 4 persons (25 litre per capita) to be installed.
 - (d) Fly ash bricks should be used as building material in the construction as per the provisions of Fly Ash Notification of September, 1999 and as amended from time to time.
- (9) PP should ensure car parking as proposed to provide porch area in each of the duplex for individual car parking and dedicated 41 ECS visitors parking. The area earmarked for the visitors parking shall be used for parking only. No other activity shall be permitted in this area in future.

(10) Air Quality and Noise

- (a) Dust, smoke & debris prevention measures such as wheel washing, screens, barricading & debris chute shall be installed at the site during construction including plastic/tarpaulin sheet covers for trucks bringing in sand & material at the site.
- (b) The exhaust pipe of the DG set must be minimum of 10mtr away from the building or incase it is less than 10m away, the exhaust pipe shall be taken up to 3m above the building.

(11) Green belt :-

- (a) PP should ensure plantation at least 15% of the project area. Plantation should be done in two rows all along the periphery of the project area including Avenue plantation along the roads, trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar etc. along with ornamental varieties.
- (b) PP should ensure to initiate plantation in the project site during construction.
- (c) Every effort should be made to protect the existing trees on the plot.

B. Specific Conditions as recommended by SEAC

- (12) Fresh water requirement for the project shall not exceed 271 KLD.
- (13) The excess treated water will be used for watering of road side green area or efforts shall be made to supply this water to the construction sites for use in the construction works.
- (14) Peripheral plantation all around the project boundary shall be carried out using tree plants of large canopy. Green area at the site will be maintained by the project proponents, which would have an overall cooling effect on the surroundings

(15) STP sludge shall be filter-pressed and the de-watered sludge shall be disposed off with the MSW.

> (Ajatshatru Shrivastava) Member Secretary

Case No. 3061/2015

Case No.: To be quoted in registered cases for correspondence

- (10) Tower back up to all interruption of
 - (17) CFL/LED should be preferred over of tube lights.(18) Installation of solar photovoltaic cells for street lighting system should be provided.
 - (19) Corpus-fund should be exclusively used for the EMP.
 - (20) MSW storage area should have 48 hours storage capacity.
 - (21) PP will obtain other necessary clearances/NOC.
 - (22) Provision for physically challenged persons be made so that they easily excess pathway/derive way for their vehicles.
 - (23) Provisions shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after completion of the period.

Standard Conditions - Encl: Annex-I

Member Secretary

Date 24.6.16

Endt No. / SEIAA/ 2016 Copy to:-

- (1). Principal Secretary, Urban Development & Environment Deptt. 3rd Floor, Mantralaya Vallabh Bhawan, Bhopal.
- Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- (3). Member Secretary, MPPCB, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- (4). The Collector, District Bhopal -M.P.
- (5). The Commissioner, Municipal Corporation, Bhopal, MP
- (6). The Jt. Director, Town & Country Planning, Paryavaran Parisar, E-5, Arera Colony, Bhopal, MP
- (7). Director, I.A. Division, Monitoring Cell, MoEF, Gol, Ministry of Environment, Forest & Climate Chanage, Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi – 110 003
- (8). Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- (9). Guard file.

Encl: Standard Conditions (Annex-I)

(Ajatshatru Shrivastava Member Secretary

Case No. 3061/2015

Case No.: To be quoted in registered cases for correspondence

State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

Annex-l

Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA notification, 2006

(Building/ construction projects / area development projects & township)

A. Construction Phase

- The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
- 2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
 - 3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
 - 4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
- 5. A First Aid Room will be provided in the project both during construction and operation of the project.
- 6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- 7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- 8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.

Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control

(Dr R P Singh) Officer-in-Charge

Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge

I of 6

State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

- 11. The dlesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- 12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- 13. Wastewater generated from temporary leabour tents will be diverted to the sewer network
- 14. No water logging should take place at any point during construction phase.
- 15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
- 16. As far as possible ready mixed concrete should be used in construction work.
- 17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- 18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/ MPPCB.
- 19. Storm water control and its use should be as per CGWB and BIS standards for various
- 20. Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- 21. Care shall be taken during the wet drilling activities.
- 22. Spread of contaminated water should be prevented by installing temporary barriers of
- 23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
- 24. On-site burning of waste material will not be permitted.
- 25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
- 26. Commitment towards CSR have to be followed strictly.
- 27. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
- To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
- 30. Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- 31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- 32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.

B. Operation Phase

- 1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, Gol before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
- 2. Treated waste water should not be used for air conditioning.
- 3. Treatment of 100% grey water by decentralized treatment should be done.
- The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
- Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
- The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
- 7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and confirm to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madhya Pradesh Pollution Control Board.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 3 of 6

Used Vide Mals 152 LANEPCO

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 8. No water logging should take place at any point during operation phase.
- The Project Proponent shall explore the possibility of using solar energy wherever possible.
- 10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam, 1984.
- 11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
- 13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- 14. Rain water harvesting for roof run- off and surface run- off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- 16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- 17. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, Gol in three months time.
- 18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
- 19. The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge 4 of 6

Party Villa 2151 SEAVERO

State Environment Impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

C. Others

- All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
- All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
- The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, GoI, and its Regional Office located at Bhopal.
- The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
- The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
- The project proponent shall also submit six monthly reports on 1st June and 1st December
 of each calendar year on the status of compliance of the stipulated EC conditions
 including results of monitored data to the regulatory Authority in hard and soft copies.
- The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report. Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, Gol at Bhopal and MPPCB.
- 10. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
- 12. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.

(Dr R P Singh)
Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

State Livit offinent impact Assessment Authority, M.P.

(Government of India, Ministry of Environment & Forests)

Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1,991 and EIA Notification, 2006.
- 15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
- 16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.
- 17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.

 Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

(Dr R P Singh)

Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 6 of 6

Issued Nider 215158EIA A FEBO