

State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment & Forests)

Environmental Planning Coordination Organization (EPCO)
Paryavaran Parisar, E-5. Arera Colony
Bhopal-4620 16

visit us http://www.mpseiaa.nic.in Tel:0755-2466970, 2466859

Fax: 0755-2462136

No:

/SEIAA/2015

Date:

To, Shri Ashish Modi, Director M/s Milan Realities 2006 Oasis Trade centre, 20/22, Yeshwant Niwas Road, Indore-MP

Sub:- Case No. 497/2010, Prior Environmental Clearance for High-rise multi storied residential project Khasra No. 84/3/4K, 84/3/4Kha, 89/1, 89/2, 90,91/2/2, 91/2/1, at Village Bicholi Mardana, Indore (MP), total land area 26660 sqm. (2.666 ha) and built up area after expansion 38038.12 sqm. (existing 17200 sqm) by M/s Milan Realities through Shri Ashish Modi, Director 2006 Oasis Trade centre, 20/22, Yeshwant Niwas Road, Indore (MP)

Ref: Your application dtd. 07.12.09 received in SEIAA office on 04.01.2010

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14th September 2006 and its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- (i). The proposed project is "High-rise multi storied residential project" having total built up area 38038.12 sq.m after expansion (existing 17200 sqm). The project comes under 8(a) category (B) of schedule of EIA Notification, 2006 because total construction is between 20,000 sqm & 1, 50,000 sqm and plot area is less than 50 ha.
- (ii). The total land area is 26660 sq.m (T & CP, Indore letter no. 5458 dtd.15.10.08) at Village Bicholi Mardana, Indore (MP). As per Khasara Panchsala 2010-2011 the landownership is the name of Mrs. Payal W/o Shri Ashish Modi & Mrs Pooja W/o shri Anurag Modi. The project involves the construction of Residential, club house, Shops & Offices.

(Ajats

(Ajatshatru Shrivastava) Member Secretary

- (iii). Project has achieved precertification from Indian Green Building Council (IGBC) under the IGBC Green Homes Rating in May 2011.
- (iv). The source of water supply is Municipal Corporation, Indore (letter dtd 23.03.15). After expansion the total water requirement is 621 KLD (fresh water 214 KLD). The waste water generation is 478 KLD and STP capacity is 478 KLD. The net treated waste water is 407 KLD which is proposed to be 100% recycled (250 KLD in flushing + 157 KLD for gardening & road wetting).
- (v). The MSW (1100 kg/day) is proposed to be collected door to door, segregation at source with twin bin waste collection system, sale of recyclable waste to recycler and composting of bio-degradable organic waste for horticulture uses. Final disposal shall be through Municipal Corporation Indore.
- (vi). Fire fighting arrangement proposed by PP includes fire water storage tank (underground & over head), fire pump, hydrant system, wet risers as per NBC 2005.
- (vii). The total power requirement is 1716 KVA. PP has also proposed power backup 1 D.G. sets capacity 250 KVA. The source of power supply is MP Electricity Board.
- (viii). The maximum height of building is 24 m. The front road width is 30 m, Front MOS 12 m and side and rear MOS 6 m & 9 m.
- (ix). PP has proposed to provide total parking for 380 ECS (Stilt 6002.5 sqm for 200 ECS and basement 6310 sq.m. for 180 ECS).
- (x). PP has proposed to provide roof top rain water harvesting through recharging pits (4 nos) for artificial recharge of ground water.
- (xi). PP has proposed an area of 4885 sq.m. (18.32%) (Existing 1900 sq.mt & for expansion 2985 sqm.) to be developed as green area.

Based on the information submitted at Para i to xi above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 190th meeting held on 24.03.15 and decided to accept the recommendations of SEAC meetings 49th dtd 23.10.10, 76th dtd 07.01.11, 84th dtd 09.11.11 & 167th dtd 10.01.15

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14th September 2006 to the proposed building construction for Highrise multi storied residential project Khasra No.84/3/4K, 84/3/4Kha, 89/1, 89/2, 90, 91/2/2, 91/2/1, at village Bicholi Mardana, Indore (MP), total land area 26660 sqm. (2.666 ha) and built up area after expansion 38038.12 sqm. (existing 17200 sqm) by M/s Milan Realities through Shri Ashish Modi, Director 2006 Oasis Trade centre, 20/22, Yeshwant Niwas Road, Indore-MP subject to the compliance of the Standard Conditions enclosed at **Annex-I** and the following additional Specific Conditions as recommended by SEIAA & SEAC in its meetings.

(Ajatshatru Shrivastava) Member Secretary

(D)-

A. Specific Conditions as recommended by SEIAA

- (1) The entire demand of fresh water should be met from Municipal supply and there should be no extraction of ground water.
- (2) PP should ensure zero discharge and the discharge of extra treated waste water (if any) should be linked with municipal sewer line.
- (3) PP should provide compactors for MSW and ensure linkage with Indore Municipal Corporation for final disposal of MSW.
- (4) PP should ensure road width and open spaces as per MP Bhumi Vikas Niyam 2012 rule 42 (1) for building up to 24 m height.
- (5) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Nagar Nigam, Indore) incorporating all the fire fighting measures recommended in National Building Code part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Nagar Nigam only after ensuring that all fire fighting measures are physically in place.
- (6) PP should ensure installation of photovoltaic cells (solar energy) for lighting in common areas, LED light fixtures and energy efficient equipments.
- (7) PP should ensure car parking as per Rule no. 84 (1) of MPBVR 2012.

(8) Green Belt:

- i. PP should ensure plantation in 25% of the total plot area.
- ii. Plantation should be done in two rows all along the periphery of the project area, recreational activity area and avenue plantation along the roads with one tree per 100 sq. m. of the plot area. PP should ensure plantation of the trees of indigenous local varieties like Neem, Peepal, Kadam, Kachnaar etc along with ornamental varieties.
- Every effort should be made to protect the existing trees on the plot.
- iv. The occupancy certificate to the building should be issued only when the authority (Nagar Nigam Indore) is satisfied that the provisions of the rule no. 67 MPBVR 2012 have been complied with.

B. Specific Conditions as recommended by SEAC

- (9) PP has to strictly follow the directions / guidelines issued by MoEF, CPCB and other Govt. Agencies from time to time.
- (10) ECBC guidelines have to be followed along with the Green building criteria.
- (11) Un-interrupted operation of STP has to be ensured.
- (12) PP shall promote schemes for conservation of water in such a way that the fresh water demand shall not go beyond 214 KLD.

(Ajatshatru Shrivastava) Member Secretary

0

Case No. 497/2010

- (13) All sanitary fittings, pipelines etc. used in the project shall be of premium quality conforming the norms to avoid wastage of water through leakages.
- (14) The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
- (15) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. The safe disposal of wastewater and solid wastes generated during the construction phase should be ensured.
- (16) All topsoil excavated during construction activities should be stored for use in horticultural / landscape development within the project site.
- (17) Disposal of debris including the excavated material during construction phase shall not create adverse effect on neighbouring communities and disposed off taking the precautions for general safety and health aspects only at the approved sites with the approval of the competent authority.
- (18) Diesel generator sets proposed as backup power shall be of enclosed type and conform to prescribed standards under EPA rules. All exhausts shall be 5.5 m above roof top. Necessary acoustic enclosures shall be provided at diesel generator set to mitigate the impact of noise.
- (19) Vehicles hired for bringing construction material at site should be in good conditions and conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- (20) Ambient noise levels should conform to residential standards both during day and night. Incremental pollution load on the ambient air and noise quality should be closely monitored during construction phase. Readymade mix concrete should be used as far as possible.
- (21) Water demand during construction should be reduced by use of curing agents, plasticizers and other best practices.
- (22) Fixtures for showers, toilet, flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- (23) Fly ash should be used as building material in the construction as per provisions of Fly Ash Notification under EPA.
- (24) Structural design aspects in accordance to the seismic zone shall be strictly adhered to.
- (25) The construction materials and debris shall be properly stored and handled to avoid negative impacts such as air pollution and public nuisances by blocking the roads and public passages.
- (26) The applicant shall install and operate their own sewage treatment plant (STP) as per the details submitted to the SEAC. The treated sewage shall be reused and recycled. In case of discharge of the treated sewage from the STP it shall conform to the norms specified by M.P. Pollution Control Board after obtaining necessary permission.

(Ajatshatru Shrivastava) Member Secretary

Case No. 497/2010

Issued vide letter no. .291-12... dated 2:5:.15

- (27) Best available technology (BAT) such as Ultra violet radiation shall be used for disinfection of sewage before reuse / recycle / discharge.
- (28) Dual plumbing system as proposed shall be adopted for the re-use of treated waste water.
- (29) Rain water harvesting for roof run-off and surface run-off, as per the plan submitted shall be implemented. Before recharging the surface run off, pretreatment must be done to remove suspended matter.
- (30) The Municipal Solid Waste shall be properly collected and segregated at source. The recyclable material shall be sold to proper vendor and other garbage shall be disposed to the sanitary landfill site of Municipal Corporation.
- (31) The applicant shall install the electric utilities / devises, which are energy efficient and meeting with the Bureau of Energy Efficiency norms, wherever applicable.
- (32) The energy audit shall be conducted at regular interval for the project and the recommendations of the Audit report shall be implemented with spirit. 26. The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- (33) The area earmarked as green area shall be used only for greenbelt and shall not be altered for any other purpose. Further, the applicant shall carry out tree plantation activity in consultation with the Municipal Corporation and local authorities within a period of 5 years.
- (34) Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Necessary signage including continuous display of status of parking availability at entry, exit and all other appropriate places shall be provided which should have appropriate size of letters and shall be visible from the at least 50 meter distance from the adjacent road. No public space shall be used or blocked for the parking and the trained staff shall be deployed to guide the visitors for parking and helping the senior citizens and physically challenged people.
- (35) Common utilities like drinking water facility, Toilets etc. shall be provided on each floor with adequate signage thereof. Adequate distance shall be maintained between the drinking water and toilet blocks.
- (36) Necessary emergency lighting system along with emergency power back up system shall be provided. In addition, emergency public address system arrangement and signage for emergency exit route shall be provided on each floor.
- (37) Necessary auto glow signage at all appropriate places shall be provided to guide the people towards exits and assembly points during the unforeseen emergency and eventuality conditions.
- (38) Training to the staff for the first aid and fire fighting along with regular mock drill shall be made an integral part of the disaster management plan of the project.

(Ajatshatru Shrivastava) Member Secretary

10)

Case No. 497/2010

Issued vide letter no. .. 89/-9.4. dated 2:5:15-

Case No.: To be quoted in registered cases for correspondence

- (39) All the statutory clearances such as the approvals for storage of diesel from Chief controller of Explosives, Fire Department, Civil Aviation Department, if applicable, shall be obtained by the applicants from the competent authorities.
- (40) Roof should meet regulatory requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirements.
- (41) Use of glass shall be minimal to reduce the electricity consumption and load on air conditioning.
- (42) Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system of the project.
- (43) Environment Management Cell shall be formed, which will supervise and monitor the Environment related aspects of the project during construction and operational phases in addition to observance of Madhya Pradesh Building and other Construction Workers Rules.

Standard Conditions - Encl: Annex-I

(Ajatshatru Shrivastava) Member Secretary

Endt No. 892 / SEIAA/ 15 Dated 2.5.15 Copy to:-

- Principal Secretary, Urban Development & Environment Deptt. 3rd Floor, Mantralaya Vallabh Bhawan, Bhopal.
- Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution (2). Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- Member Secretary, Madhya Pradesh Pollution Control Board, Paryavaran (3). Parisar, E-5, Arera Colony, Bhopal-462016.
- The Collector, Distt-Indore -M.P.
- (5). The Commissioner, Municipal Corporation, Indore, MP
- The Jt. Director, Town & Country Planning, Indore, MP
- Director, I.A. Division, Monitoring Cell, MoEF, Gol, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi - 110 003
- Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- Guard file. (9).

Encl: Standard Conditions (Annex-I)

(Ajatshatru Shrivastava) Member Secretary

l. Mohn

Case No. 497/2010

Issued vide letter no. 891. 72.... dated 2:5:15

Case No.: To be quoted in registered cases for correspondence

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madriya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

Annex-I

Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA notification, 2006 (Building/ construction projects / area development projects & township)

A. Construction Phase

- The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.
- 2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
- 3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile foilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
- 4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
- A First Aid Room will be provided in the project both during construction and operation of the project.
- 6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.

 Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

1 of 6

Issued Vide 2 991-92 EIAN/EPCO

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

- 11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for
- 12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- 13. Wastewater generated from temporary leabour tents will be diverted to the sewer network
- 14. No water logging should take place at any point during construction phase.
- 15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
- 16. As far as possible ready mixed concrete should be used in construction work.
- 17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- 18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated
- 19. Storm water control and its use should be as per CGWB and BIS standards for various
- 20. Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- Care shall be taken during the wet drilling activities.
- 22. Spread of contaminated water should be prevented by installing temporary barriers of
- 23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
- 24. On-site burning of waste material will not be permitted.
- 25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
- 26. Commitment towards CSR have to be followed strictly.

27. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge

2 of 6

Issued Vide no 2.5-10 HELAA/EPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

- 28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
- To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
- Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- 31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- 32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.

B. Operation Phase

- 1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, Gol before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
- Treated waste water should not be used for air conditioning.
- Treatment of 100% grey water by decentralized treatment should be done.
- The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
- Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
- The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
- 7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and confirm to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madhya Pradesh Pollution Control Board.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

3 of 6

Issued Vale In 891-98 SELANEPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- No water logging should take place at any point during operation phase,
- The Project Proponent shall explore the possibility of using solar energy wherever possible.
- 10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam, 1984.
 - 11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
- 13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- 14. Rain water harvesting for roof run- off and surface run- off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- 16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- 17. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, Gol in three months time.
- 18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
- The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

4 of 6

Officer-in-Charge

Dated & S. 10 991-92 ELAN EPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4820 16

C. Others

- All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
- All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
- The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, GoI, and its Regional Office located at Bhopal.
- The Ministry or any other competent authority may alter/modify the conditions or stipulate
 any further condition in the interest of environment protection.
- The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
- The project proponent shall also submit six monthly reports on 1st June and 1st December
 of each calendar year on the status of compliance of the stipulated EC conditions
 including results of monitored data to the regulatory Authority in hard and soft copies.
- The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report. Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, Gol at Bhopal and MPPCB.
- 10. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
- 12. The SEIAA of M.P. reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.

(Dr R P Singh)
Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

5 of 6

Issued Vide Nr. 871-12 SELA VEPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.
- 15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
- 16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.
- 17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.

20. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

(Dr R P Singh)
Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

6 of 6

housed Vide for 2. Sets a/Epr