

State Environment Impact Assessment Authority, M.P. (Government of India, Ministry of Environment Forest & Climate Change)

Environmental Planning Coordination Organization (EPCO)
Paryavaran Parisar, E-5. Arera Colony
Bhopal-4620 16

visit us http://www.mpseiaa.nic.in Tel:0755-2466970, 2466859

Fax: 0755-2462136

No: 607 /SEIAA/2017 Date: 9.6.12

To, Shri Rohit Wadhwa (Director) M/s Blue Lotus Realtors Pvt. Ltd. Krishna Kunj, Gandhi Road, Gwalior (MP)-474011

Sub:- Case No. 5199/2016: Prior Environmental Clearance for Proposed Residential & Commercial Project "The Olympia" at Village - Ramaua, Tehsil & District - Gwalior, MP, Total Land area -78060.00 sq.m. (7.806 ha) & Total Built up Area- 142710.17 sq.m. by M/s Blue Lotus Realtors Pvt. Ltd. through Director Shri Rohit Wadhwa, Krishna Kunj, Gandhi Road, Gwalior (MP)-474011, Ph. No. 0751-3204400, Email : infor@bluelotus.co.in. Env. Consultant: In situ Enviro Care, Bhopal (M.P)

Ref: Your application dtd. 26.04.16 received in SEIAA office on 13.05.2016

With reference to above, the proposal has been appraised as per prescribed procedure & provisions under the EIA notification issued by the Ministry of Environment & Forests vide S.O. 1533 (E), dated 14th September 2006 and its amendment, on the basis of the mandatory documents enclosed with the application viz., Form I, Form IA, Conceptual Plan, drawings, ppt & the additional clarifications furnished in response to the observations by the State Expert Appraisal Committee (SEAC) and State Environment Impact Assessment Authority (SEIAA) constituted by the competent Authority.

- (i). The proposed project is Building and Construction Residential & Commercial Project "The Olympia" having total built up area 142710.17 sq. m. and the total land area is 78060.00 sq.m. (7.806 ha). The project comes under 8(a) category (B) of schedule of EIA Notification, 2006 because total construction is between 20, 000 sq.m & 1, 50,000 sq. m and plot area is less than 50 ha.
- (ii). As per T & CP Gwalior approval (vide let no. 903 dtd.23.08.14) the total land area is 78060.00 sq.m. (7.806 ha) at Village- Ramaua, Tehsil & District Gwalior (M.P.). As per Khasara Panchsala 2013-14 the land name of M/s Blue Lotus Realtors Pvt. Ltd. through Director Shri Rohit Wadhwa. The project includes construction of 13 blocks (Res. 8, School 1, Club House 1, Community Hall 1, Commercial 1, Duplex Block 1,) including Residential 1424, studios 273, duplex 14, EWS 117, Convenient Shop 10,Club House 1 Unit.
- (iii). The source of water supply is Gwalior Municipal Corporation (letter dtd. 28.08.15) from Nagar Nigam Gwalior. The total water requirement is 1234 KLD fresh water 762 KLD. The waste water generation is 1048 KLD and STP

Case No. 5199/2016

Issued vide letter no. .. 6.07...8 dated 2.6.12

Case No.: To be quoted in registered cases for correspondence



- capacity is 1100 KLD. The available treated water is 944 KLD, out of which 498 KLD shall be recycled & 446 KLD will be disposed in municipal sewer line. (Gwalior Municipal Corporation letter dtd. 09.07.2015).
- (iv). It is noted that a Nallah is passing through the site from North to South. For protection of nallah, PP has proposed to create buffer zone in two rows of plantation along the nallha. PP has submitted commitment letter (dtd. 16.08.16) regarding construction activity will be initiated at least 15m away from the adjoining nallah.
- (v). The MSW (4.12TPD) shall be generated which is proposed to be segregated at source and collected in bins of three colors (green, blue and dark grey) separate for biodegradable and non biodegradable waste. Final disposal shall be through Municipal Corporation Gwalior.(GMC letter dtd. 14.08.15)
- (vi). The maximum height of the building is 30 m. PP has provided road width 24 m; Front MOS 12m and side / rear MOS 7.50 m.
- (vii). PP has proposed to provide hose reel, extinguishers, wet riser, yard hydrants, sprinkler system, automatic fire detection, alarm system etc. as per NBC 2005. PP has submitted Fire fighting provisional NOC issued from Nagar Palika Nigam Gwalior dtd. 02.12.15.
- (viii). PP has submitted roof top rain water harvesting system for ground water recharging through recharge pits (10 nos.).
- (ix). PP has proposed to provide parking for 2749 ECS (1974 ECS for residential and 775 ECS for commercial. (Basement- 1292 ECS; Stilt- 1315 ECS; Open-205 ECS).
- (x). The total power requirement is 5514 KVA for residential and 1288.26 KVA for commercial. The source of electricity is Madhya Pradesh Kshetra Vidyut Vitran Company Limited Gwalior. PP has also proposed 2 DG Set for power back up capacity 1200 KVA. For energy conservation, PP has proposed installation of 75 nos of solar panel, use of LED fixtures, level controller for pumps, designing of peak & non peak circuits for common area et.
- (xi). Out of the total land area 78060.00 sq.m an area of 8069.20 sq.mt. is permitted from T & CP to be developed as green area. PP has proposed to plant 1006 nos of trees in 3 rows on periphery with 2555 ornamental trees in an additional 792.12 sq. m. area. The periphery area of the adjoining nallah is 495.56m and PP has proposed to create buffer zone by planting 297 nos. of trees in 3 rows.

Based on the information submitted at Para i to xi above and others, the State Level Environment Impact Assessment Authority (SEIAA) considered the case in its 427th meetings 188th dtd 30.03.17

Hence, Prior Environmental Clearance is accorded under the provisions of EIA notification dtd. 14th September 2006 to the proposed Residential & Commercial Project "The Olympia" at Village - Ramaua, Tehsil & District - Gwalior, MP, Total Land area -78060.00 sq.m. (7.806 ha) & Total Built up Area- 142710.17 sq.m. by M/s Blue Lotus Realtors Pvt. Ltd. through Director Shri Rohit Wadhwa, Krishna Kunj, Gandhi Road, Gwalior (MP)-474011 subject to the compliance of the

Standard Conditions enclosed at Annex-I and the following additional Specific Conditions as recommended by SEIAA & SEAC in its meetings.

A. Specific Conditions as recommended by SEIAA

- The entire demand of water should be met through Municipal Corporation, Gwalior.
- (2) The inlet and outlet point of natural drain system should be maintained with adequate size of channel for ensuring unrestricted flow of water.
- (3) Disposal of waste water.
 - (a) PP should ensure linkage with municipal sewer line for disposal of waste water. No waste water will be permitted to enter the nalla. Till such time the Municipal sewer line is laid, PP has committed to utilized extra treated waste water in other projects.
 - (b) The treated wastewater of 498 KLD shall be recycled and reused for flushing (407 KLD) gardening (66 KLD) and others (25 KLD) to reduce the demand of fresh water as committed.
 - (c) Water quality monitoring should be carried out regularly in consultation with MPPCB.
- (4) The existing nallah should be properly channelized and developed for irrigation.
- (5) PP must ensure that government land in patches located within the colony premises will be properly fenced and no government land will be used for any other purpose. PP should ensure to leave proper approach upto the government land.
- (6) PP should apply to in Central Ground Water Board and get consent from CGWB as alternative source of water supply to meet the requirement.
- (7) The storm water management should be regulated in such a way that it should not mix with the extra treated sewage water. The budget should be included in EMP for storm water management.

(8) Solid Waste Management:

- (a) Provide compactors for MSW.
- (b) Separate wet and dry bins must be provided at the ground level for facilitating segregation of waste.
- (c) The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- (9) PP should ensure road width, front MOS and side / rear as per MPBVR 2012.
- (10) For firefighting:-

- (a) PP should ensure connectivity to the fire station from the project site.
- (b) As per MPBVR, 2012 rule 42 (3) PP should submit necessary drawings and details to the Authority (Municipal Corporation, Gwalior) incorporating all the fire fighting measures recommended in National Building Code Part – IV point no. 3.4.6.1. The occupancy permit shall be issued by Municipal Council only after ensuring that all fire fighting measures are physically in place.

(11) For Rain Water Harvesting, and Ground water recharge:-

- (a) PP should ensure the rain water harvesting with 10 nos of recharging pits. In addition, PP should provide recharging trenches. The base of the trenches should be Kachha with pebbles.
- (b) Rain water harvesting for roof run- off and surface run- off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 4 mts. above the highest ground water table.
- (c) The unpaved area shall be more than or equal to 20% of the recreational open spaces.
- (12) PP should ensure to provide car parking as proposed 2749 ECS (Residential –1974 ECS & Commercial- 775 ECS) in stilt, basement and open area.

(13) For Energy Conservation PP should Ensure :-

- (a) Use of LED lights in the common areas, landscape areas, gates and boundary compound walls etc.
- (b) Install 75 nos. of Solar panel as proposed..
- (c) For power back up ensure to provide 02 no. DG set capacity of 1200 KVA
- (d) PP should also ensure to adopt energy conservation measure as per State norms.

(14) Air Quality and Noise:-

- (a) Dust, smoke & debris prevention measures such as wheel washing, screens, barricading & debris chute shall be installed at the site during construction including plastic/tarpaulin sheet covers for trucks bringing in sand & material at the site.
- (b) The exhaust pipe of the DG set if installed must be minimum of 10mtr away from the building or in case it is less than 10m away, the exhaust pipe shall be taken up to 6m above the building.
- (c) Air quality Monitoring should be carried out regularly in consultation with MPPCB.

(15) Green belt:-

- (a) PP should ensure plantation to the 8861.32 sq. m. (11.35 %) as per the proposed landscape plan by planting 3561 nos. of trees in 3 rows in the entire periphery, along the roads, around open space area, parking area and other amenities. Besides this, 297 saplings will be planted in 495.96 mt. both sides periphery of nallah in 3 rows. Trees of indigenous local varieties like Neem, Peepal, Kadam, Karanj, Kachnaar, Saptparni etc.should be planted.
- (b) No existing trees will be allowed to cut. Every effort should be made to protect the existing trees on the plot.
- (c) The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.
- (16) In the case of future expansion in the scope or any changes(s) in the scope of the project shall again require Prior Environmental Clearance as per EIA notification, 2006.
- (17) The project authorities shall earmark adequate funds to implement the conditions stipulated by SEIAA/SEAC along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.
- (18) Budget provision of Rs. 146.43 Lakhs with Rs. 28.2 lakhs per year as running cost should be made under EMP for STP, rain water harvesting, storm water and solid waste management and other activities.
- (19) Budget provision of Rs. 80.00 lakhs should be made under ESR for social welfare activities in consultation with District Administration.

B. Specific Conditions as recommended by SEAC

- (20) The excess treated water will be used for watering of municipal road side green area or efforts shall be made to supply this water to the construction sites for use in the construction works.
- (21) No construction activity should be take-up within 15 meters HFL of adjoining nallah.
- (22) Peripheral plantation all around the project boundary shall be carried out using tall saplings of minimum 2 meters height of species which are fast growing with thick canopy cover preferably of perennial green nature. PP will also make necessary arrangements for the causality replacement and maintenance of the plants.
- (23) STP sludge shall be filter-pressed and the de-watered sludge shall be disposed off with the MSW.
- (24) Power back-up for un-interrupted operations of STP shall be ensured.
- (25) CFL/LED should be preferred over of tube lights.

Case No. 5199/2016

Issued vide letter no. .6.7-8.... dated .2...6.' | 2 Case No.: To be quoted in registered cases for correspondence

- (26) Fund should be exclusively earmarked for the implementation of EMP.
- (27) MSW storage area should have 48 hours storage capacity.
- (28) Dual plumbing should be provided.
- (29) Provision for physically challenged persons be made so that they easily excess pathway/derive way for their vehicles.
- (30) Provisions shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after completion of the period.
- (31) PP will obtain other necessary clearances/NOC from respective authorities.
- (32) PP will comply with all the commitments made in by the letter dated 24/08/2016, 03/12/2016, 27/12/2016 and 02/03/2017.

(Anupam Rajam)
Member Segretary

Endt No. 6 0 8 SEIAA/ 17 Copy to:-

Dated 6.12

- (1) Principal Secretary, Urban Development & Environment Deptt. 3rd Floor, Mantralaya
- (2). Secretary, SEAC, Research and Development Wing Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5, Arera Colony Bhopal-462016.
- (3). Member Secretary, MPPCB, Paryavaran Parisar, E-5, Arera Colony, Bhopal-462016.
- (4). The Collector, Distt- Gwalior -M.P.

Vallabh Bhawan, Bhopal.

- (5). The Commissioner, Municipal Corporation, Gwalior, MP
- (6). The Jt. Director, Town & Country Planning, GDA Building Ravi Nagar, Gwalior (M.P.)
- (7). Director, I.A. Division, Monitoring Cell, MoEF, GoI, Ministry of Environment & Forest Indira Paryavaran Bhawan, Jor Bagh Road, New Delhi 110 003
- (8). Director (S), Regional office of the MOEF, (Western Region), Kendriya Paryavaran Bhawan, Link Road No. 3, Ravi Shankar Nagar, Bhopal-462016.
- (9). Guard file.

Encl: Standard Conditions (Annex-I)

(Dr. Sanjeev Sachdev) Officer-in-Charge

(Government of India, Ministry of Environment & Forests) Research and Development Wing, Madhya Pradesh Pollution Control Board, Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

Annex-L

Standard Conditions related to under item 8 (a) & 8 (b) of the schedule of EIA notification, 2006 (Building/ construction projects / area development projects & township)

A. Construction Phase

The construction site shall be provided with adequately barricades of at least 3 m height on its periphery with adequate signage.

- 2. All required sanitary and hygienic measures should be in place before starting any construction work and are to be maintained throughout the project phase.
 - 3. Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.
 - 4. Occupational health and safety measures for the workers including identification of work related health hazards, training on malaria eradication, HIV, and health effects on exposure to dust etc. shall be carried out. Periodic monitoring for exposure to respirable dust on the workers shall be conducted and records maintained including health records of the workers. Awareness programme for workers on impact of dust on their health and precautionary measures like use of personal equipments etc. shall be carried out periodically.
 - 5. A First Aid Room will be provided in the project both during construction and operation of the project.
- 6. All the topsoil excavated during construction activities should be stored for use in horticulture/landscape development within the project site.
- 7. Disposal of muck during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- 8. Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dump sites for such material must be secured so that they should not leach into the ground water.

10. Any hazardous waste generated during construction phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.

Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge

1 of 6

NSRUED XIDE N 609-8 SELANTERCO Dated 2 6 2

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5, Arera Colony, Bhopal-4620 16

- 11. The diesel generator sets (if any) to be used during construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- 12. The diesel required (if any) for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- 13. Wastewater generated from temporary leabour tents will be diverted to the sewer network in the area.
- 14. No water logging should take place at any point during construction phase.
- 15. If the project site is located within the 100 km of Thermal Power Stations, then fly ash should be used as building material in the construction as per the provisions of Fly ash Notification of September, 1999 and amended as on 27th August, 2003.
- 16. As far as possible ready mixed concrete should be used in construction work.
- 17. Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- 18. Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/ MPPCB.
- Storm water control and its use should be as per CGWB and BIS standards for various applications.
- Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- 21. Care shall be taken during the wet drilling activities.
- 22. Spread of contaminated water should be prevented by installing temporary barriers of G.I. Sheets.
- 23. To prevent surface and ground water contamination by oil/grease, leak proof containers shall be used for storage and transportation of oil/grease. The floors of oil/grease handling area will be kept effectively impervious.
- 24. On-site burning of waste material will not be permitted.
- 25. Ground water should not be used during construction phase. Private tanker water suppliers may be asked to supply water during construction phase.
- 26. Commitment towards CSR have to be followed strictly.

27. Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

(Dr R P Singh). 411

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge

2 of 6

Issued Vide No. 607-8 HAATEPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 28. Wherever possible, the area around the STP / ETP should be surrounded with dense green belt.
- 29. To reduce the electricity consumption and load on air conditioning, high quality double glass with special reflective coating in windows should be promoted.
- Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- 31. Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air-conditioned spaces while it is aspirational for non-air conditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- 32. Approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.

B. Operation Phase

- 1. The installation of the Sewage Treatment Plant (STP) as submitted by PP in the office of SEIAA should be certified by an independent expert and a report in this regard should be submitted to the Regional office of the Ministry of Environment & Forest, GoI before the project is commissioned for operation. Treated effluent discharge from STP shall be recycled/reused to the maximum extent possible. Treated effluent shall conform to the norms and standards of the M.P. Pollution Control Board. Necessary measures should be made to mitigate the odour problem from STP.
- Treated waste water should not be used for air conditioning.
- 3. Treatment of 100% grey water by decentralized treatment should be done.
- The bio-medical waste (if applicable) generated should be disposed off as per the provisions of Bio-medical waste (Management and Handling) Rules 1988 as amended till date.
- Provision of separate entrance / exit gate should be made for collection of segregated bio-medical waste (if applicable) from the storage area.
- The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material as per CPCB norms.
- 7. Diesel power generating sets if proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and confirm to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. Low sulphur diesel must be used. The location of the DG sets may be decided with in consultation with Madnya Prades Pollution Control Board.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 3 of 6

Issued Vide No. 6.07 - 8-11AACESCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 8. No water logging should take place at any point during operation phase.
- The Project Proponent shall explore the possibility of using solar energy wherever possible.
- 10. Provision for plantation has to be made as per Madhya Pradesh Bhumi Vikas Niyam,
 - 11. Any hazardous waste generated during operation phase, should be disposed off as per applicable rules and norms with necessary approvals of the M.P. Pollution Control Board.
- Noise should be controlled to ensure that it does not exceed the prescribed standards of CPCB.
- 13. Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- 14. Rain water harvesting for roof run- off and surface run- off, should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The bore well for rainwater recharging should be kept at least 5 mts. above the highest ground water table.
- The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- 16. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking should be fully internalized and no public space should be utilized.
- 17. A Report on the energy conservation measures confirming to energy conservation norms finalize by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Regional office of Ministry of Environment & Forest, GoI in three months time.
- 18. Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
- 19. The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.
- The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
- Ozone Depleting Substances (Regulation & Control) Rules shall be followed while designing the air conditioning system (if any) of the project.

(Dr R P Singh) Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 4 of 6

Personal Wide No 60 7 8 SEIANEPCO

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

C. Others

- All activities / mitigative measures proposed by PP in Environmental Impact Assessment (if applicable) and approved by SEAC must be ensured.
- All activities / mitigative measures proposed by PP in Environmental Management Plan and approved by SEAC must be ensured.
- All parameters listed in Environmental Monitoring Plan approved by SEAC must be monitored at approved locations and frequencies.
- 4. Project Proponent has to strictly follow the direction/guidelines issued by MoEF, CPCB and other Govt. agencies from time to time.
- The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year wise expenditure shall be reported to the MoEF, GoI, and its Regional Office located at Bhopal.
- 6. The Ministry or any other competent authority may alter/modify the conditions or stipulate any further condition in the interest of environment protection.
- The Environmental Clearance shall be valid for a period of five years from the date of issue of this letter.
- The project proponent shall also submit six monthly reports on 1st June and 1st December
 of each calendar year on the status of compliance of the stipulated EC conditions
 including results of monitored data to the regulatory Authority in hard and soft copies.
- The Regional Office, MoEF, Gol, Bhopal and MPPCB shall monitor compliance of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report. Environmental Management Plan and other documents information should be given to Regional Office of the MoEF, Gol at Bhopal and MPPCB.
- 10. The Project Proponent shall inform to the Regional Office, MoEF, Gol, Bhopal and MP PCB regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.
- 11. In the case of expansion or any change(s) in the scope of the project, the project shall again require prior Environmental Clearance as per EIA notification, 2006.
- 12. The SEIAA of M.P. reserves the right to add additional safeguard, measures subsequently, if found necessary, and to take action including revoking of the environment clearance under the provisions of the Environmental (Protection), Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.
- 13. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained (as and when applicable), by the project proponent from the respective competent authorities.

(Dr R P Singh)
Officer-in-Charge

(Dr Vinita Vipat) Officer-in-Charge (Dr Sadhna Tiwari) Officer-in-Charge 5 of 6

Issued Wide Nov. 603 STANEPED O

(Government of India, Ministry of Environment & Forests)
Research and Development Wing, Madhya Pradesh Pollution Control Board,
Paryavaran Parisar, E-5. Arera Colony, Bhopal-4620 16

- 14. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1,991 and EIA Notification, 2006.
- 15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company and in the public domain.
- 16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the Regional Office of MoEF.
- 17. Concealing factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of Environment (Protection) Act, 1986.
- 18. A copy of the environmental clearance shall be submitted by the Project Proponent to the Heads of the Local Bodies, Panchayat and municipal bodies as applicable in addition to the relevant officers of the Government who in turn has to display the same for 30 days from the date of receipt.
- 19. The Project Proponent shall advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at website of the State Level Environment Impact Assessment Authority (SEIAA) at www.mpseiaa.nic.in and a copy of the same shall be forwarded to the Regional Office, MoEF, Gol, Bhopal.

20. Any appeal against this prior environmental clearance shall lie with the Green Tribunal, if necessary, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

(Dr R P Singh)
Officer-in-Charge

arge

(Dr Vinita Vipat) Officer-in-Charge

(Dr Sadhna Tiwari) Officer-in-Charge 6 of 6

Daied 2 6 12